

LIGHTWEIGHT & DURABLE ALUMINIUM COMPOSITE PANEL WITH A FLUTED POLYETHYLENE CORE

Why use ALUFLUTE?



Easy to install



Uniform, flat surface



Lightweight yet rigid



Highly resistant to weather



5

Versatile and easily formable

Five Year Guarantee for indoor and outdoor use

Applications





POS Displays Sign making



Kiosks



ALUFLUTE features a corrugated plastic core sandwiched between two 0.30mm aluminium skins that are coated with a superior polyester paint finish. This innovative core structure produces a strong lightweight panel, offering easy handling and providing maximum strength and stability.

ALUFLUTE has an easy-peel protective film and is the perfect base for vinyl.

ALUFLUTE panels are rigid, easy to install and can be easily fabricated for folding and forming and they are much lighter than standard Aluminium Composite Panels.

Colour Ultra-White Gloss/Matt Panel Thickness (mm) 5mm 6mm 10mm Weight (kg/m?) 3.3 3.5 5.1kg Skin PE coated Aluminium Skin Thickness 0.3mm Core Fluted Polyethylene Neet Sizes Width Length 1220 2440 1220 3050 Adhesive Layer 9 Digital Paint Finish 9 Frotective Film 9 Protective Film	operty			
Weight (kg/m²)3.33.55.1kgSkinPE coated AluminiumSkin Thickness0.3mmCoreFluted Polyethyleneheet SizesWidthLength1220244012203050I Adhesive LayerI Adhesive LayerI Digital Paint FinishI Huminium Skin	Colour	Ultra-White Gloss/Matt		
Skin PE coated Aluminium Skin Thickness 0.3mm Core Fluted Polyethylene heet Sizes Width Length 1220 2440 1220 3050 1 Adhesive Layer 1 Digital Paint Finish 1 Fluted Core 1 Aluminium Skin	Panel Thickness (mm)	5mm	6mm	10mm
Skin Thickness 0.3mm Core Fluted Polyethylene heet Sizes Width Length 1220 2440 1220 3050 Adhesive Layer Digital Paint Finish Fluted Core Aluminium Skin	Weight (kg/m²)	3.3	3.5	5.1kg
Core Fluted Polyethylene heet Sizes Vidth Length 1220 2440 1220 3050 1220 3050 120 3050	Skin	PI	E coated Alumini	um
heet Sizes Width Length 1220 2440 1220 3050 1 Adhesive Layer 2 Digital Paint Finish 3 Fluted Core 4 Aluminium Skin	Skin Thickness		0.3mm	
Width Length 1220 2440 1220 3050 Adhesive Layer Adhesive Cayer Adhesive Layer Adhesive Layer Adhesive Layer Adhesive Layer Adhesive Layer Adhesive Layer Adhesive Layer	Core	Fluted Polyethylene		
1220 2440 1220 3050 1 Adhesive Layer 2 Digital Paint Finish 3 Fluted Core 4 Aluminium Skin				
 Adhesive Layer Digital Paint Finish Fluted Core Aluminium Skin 	0			- MILL
	1220 3050	 2 Digital F 3 Fluted C 4 Aluminiu 	aint Finish ore ım Skin	



Tel +1 718 841 9940

USA Office

For more information or to contact your local Sales Manager or Distributor

Call +44 (0) 1392 823015 www.multipaneluk.co.uk